2024 Ubbink. All rights reserved.1 Content is subject to change without notice. Availability and configurations may differ per country. I UB-19-12-2024-INT-EN

Air Excellent distribution box DB212V125-200HE 12 connections




Article number: 188962

Product introduction

The Air Excellent horizontal DB212 is designed to radially distribute air from a ventilation unit, minimizing system pressure drop, fan energy use, and sound levels. It is compatible with Aerfoam insulated ducts and features 12 Air Excellent AE34C duct connections. With DBOX adaptors, it can connect to any duct diameter within the Air Excellent range. The compact box is ideal for small spaces, it can be installed on ceilings, walls, or floors.

- Includes stepped adaptor, 12 internal air restrictor rings, and 6 covers for unused connections
- Ideal for optimizing space in small areas
- Made of durable, rust-free, lightweight plastic (PP) for easy handling and installation
- Airtight mechanical connections to minimize pressure loss, fan energy consumption, and sound levels

Product dimensions





© 2024 Ubbink. All rights reserved.1 Content is subject to change without notice. Availability and configurations may differ per country. I UB-19-12-2024-INT-EN

Air Excellent distribution box DB212V125-200HE 12 connections



Article number: 188962

Technical specifications

Specifications	
Technical	
Colour	Grey
Material	PP
Anti static	\checkmark
Antimicrobial	\checkmark
Performance	
Temperature resistance (min.)	-20 °C
Temperature resistance (max.)	60 °C
Reaction to fire: Euro class	E
Dimensions	
Length gross	598 mm
Width	318 mm
Height	257 mm
Net weight	2.192 kg

© 2024 Ubbink. All rights reserved.1 Content is subject to change without notice. Availability and configurations may differ per country. I UB-19-12-2024-INT-EN

Air Excellent distribution box DB212V125-200HE 12 connections



Article number: 188962

Technical details

Pressure Loss Dbox	
Δp (Pressure Loss) [Pa]	
1,0	
2,0	
3,0	
4,5	
7,0	
9,0	
12,0	
14,0	
16,0	
23,0	
28,0	

Figures are based on measurements by the TÜV SÜD.